Specifications

Collators DFC-100 Collating Stations 10 (2 tower option for 20)

3 wheel friction feed Feed System **Capacity Per Station** 28 mm (260 mm sheets @ 80 gsm)

Sheet Size Min 140 x 160 mm **Sheet Size Max** 320 x 450 mm **Paper Weight** 52.3 - 127.9 gsm Speed (sets/hr) 4200 sets / hour

Programmes Interleave insertion mode, block mode, alternate mode, normal mode Total / batch Counters

Detection Systems Miss

Yes Yes Double - Feed Yes Yes No Paper Yes Yes Stacker Full Yes Yes

Straight, offset stack

Stacking Modes Stacking Capacity Dimensions (WxDxH)

Set-Up Time

Programmes

On-Line / Off-Line

Staple Positions

Booklet Size (WxL)

Max Speed

78 mm 820 x 618 x 1000 mm

65 kg

230V 50Hz 2A **Power Supply/Consumption**

Bookletmakers DBM-120 Dynamic Bookletmaker

> Automatic size change in 14 seconds 10 pre-set sizes, 3 custom sizes Yes / Yes

80 page book (20 flat sheets) Max Book Thickness (80 gsm) Max Corner Stitch Thickness (80 gsm) 25 flat sheets

Saddle / side / corner / fold only

Up to 2,400 A5 books / hr Max (booklet) size: 320 x 225 mm Min (booklet) size: 148 x 100 mm* Max (sheet) size: 320 x 450 mm Min (sheet) size: 148 x 200 mm**

Min 139 x 210 - Max 231 x 320 mm Staple

Jam, misfeed, staple empty

Detection Systems Max Trim Cut Trim Adjustment

Side / Corner Stapling (LxW) Stitch / Staple Type

Staple Capacity Dimensions (WxDxH)

Power Supply / Consumption

1300 x 700 x 550 mm 120 kg

78 mm

820 x 618 x 1144 mm

DFC-120

140 x 160 mm

320 x 450 mm

52.3 - 127.9 gsm

4200 sets / hour

Total / batch

12 (2 tower option for 24)

28 mm (260 mm sheets @ 80 gsm)

3 wheel friction feed

74.2 kg

Straight, offset stack

230V 50Hz 2.8A

DBM-120T Trimmer

Automatic size change in 14 seconds

80 page book (20 flat sheets)

Up to 2,400 A5 books / hr Max (untrimmed) 320 x 225 mm Min (untrimmed) 148 x 100 mm Max (trimmed) 320 x 225 mm Min (trimmed) 148 x 80 mm*

Waste bin full 20 mm 0.4 mm increments

537 x 550 x 576 mm 83 kg 230V 50Hz 1.5A

230V 50Hz 1A

GROUPE

CHARLES KIEFFER

CK Business Center 2, rue Léon Laval Z.A. Am Bann L-3372 Leudelange

Tél: +352 26 380-1 Fax: 26 380-380

www.ck-online.lu www.konicaminolta.lu postprint@ck-online.lu

E-DFC100120BR/AUG08





^{*} with optional small booklet kit and DBM-120 trimmer min booklet size is 148 x 100 mm

^{**} with optional small booklet kit

Duplo



ne user-friendly control panel has several programmes including block mode for on-the-run loading and interleaving for separation of batched sets. The display has both a 'total' and ining' counter to monitor the progress of the job.

liable paper handling The 3 feed wheels ensure maximum ntact with the paper for flawless and consistent delivery.

Bond, NCR, light card and even certain coated stocks can all be fed with separator pressure and tray pressure of each bin individually

Out-of-paper, double and paper jam detectors ensure the integrity of each set.

straight or offset collating The collating tray can be run in offset mode or straight collate mode depending on the requirements of the job. The machine automatically stops when the catch tray is full so can be left to run



Duplo DFC-100 & DFC-120 collators

The vertically arranged DFC-series collators are available in 10, 12, 20 or 24 station configurations with an output speed of up to 4,200 sets/hour. On-the-run loading and bi-directional feeding enables productivity to be

maintained whilst simply collating or sending sets to the online bookletmaker.



The DBM-120 can be either hand-fed or connected online to a Duplo collator creating a 2,400 booklet/hour finishing system. Flat lying staples and the optional DBM-120T edge trimmer result in a strong and professional booklet.





quick automatic set-up

Changing between booklet sizes takes just seconds. Simply select the required size, and the side guides adjust automatically. For smaller books, the staple positions can be brought closer together if required.

four finishing modes

The Duplo mini friction collating and bookletmaking system offers smaller print enterprises,

in-plants, offices and CRDs a cost-effective solution to their finishing needs. Much of the

functionality and dependability normally reserved for much larger finishing equipment is

available as-standard in this high performance and space-efficient system.


The DBM-120 is capable of side stapling, corner stapling, folding and saddle stapling so just about any finishing requirement is possible with this versatile unit.











DFC-120 friction collating tower

hand feeding

The DBM-120 can be used as a standalone bookletmaker and manually fed through the hand feeder. This is ideal for very short run or pre-collated jobs such as those from a digital printer.

A simple toggle dial screen allows the operator to input and store up to 13 separate programs for quick recall later.



optional fore-edge trimmer

When producing thicker books it is often necessary to trim the fore-edge. The Duplo DBM-120T is an optional trimmer unit that will cut this edge as the book is ejected from the bookletmaker ensuring a highly presentable end product.



